

GTC-154-PIR / GTC-155-PIR

4.0 / 5.0 Megapixel HD Network IP IR DOME PIR Camera

KEY FEATURES

- *1/3" Progressive Scan CMOS
- *H.265/H.264 video compression
- *Up to 4MP (2592*1520) / 5MP (2592*1944) resolution
- *Day / Night auto switch
- *IR range up to 30M
- *IP66 rating



TECHNICAL SPECIFICATIONS



Model No.	GTC-154-PIR	GTC-155-PIR
Image Sensor	1/3" Progressive Scan CMOS	
Min. Illumination	0.05Lux @(F1.2,AGC ON) ,0 Lux with IR), 0 Lux with IR	
Shutter time	1/5 s ~ 1/20,000 s	
Slow shutter	Support	
Lens	3.6mm / 6.0mm	
Lens Mount	M12	
Day& Night	IR cut filter with auto switch	
Wide Dynamic Range	Digital wide dynamic	
IR LED	18pcs	
IR Range	30M	
Video Compression	H.265/H.264	
H.265 code profile	Main Profile	
Video bit rate	256K~8M	
Max. Image Resolution	4MP (2592*1520)	5MP (2592*1944)
Frame Rate	Mainstream (1-15fps optional) 4MP(2592*1520), 3MP(2048*1536), 1296P(2304*1296), 1080P(1920*1080), 960(1280*960), 720P(1280*720)	Mainstream (1-15fps optional) 5MP(2592*1944), 4MP(2592*1520), 3MP(2048*1536), 1080P(1920*1080), 960(1280*960), 720P(1280*720)
	Substream VGA(640*480), QVGA(320*240)	
	Mobilestream QVGA(320*240)	
Image Settings	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser	
Day/Night Switch	Auto/Schedule/Triggered by Alarm In	
Network Storage	NA	
Alarm Trigger	NA	

Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Security	Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, IP address filtering
System Compatibility	ONVIF 2.4,RSSP
Communication Interface	1 RJ45 10M / 100M Ethernet interface
Reset Button	NA
POE	Support(built in)
SD card	NA
Audio	NA
Waterproof Connector	Tail wire RJ45 interface for waterproof interface +
Operating Conditions	-10 °C ~ 60 °C (-22 °F ~ 140 °F)Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 10%, PoE (802.3af)
Power Consumption	Max. 5 W (Max. 7 W with IR cut filter on)
Weather Proof	IP66
Dimensions	115.28*115.28*102.29MM
Weight	469g

**Design and specifications are subject to change without prior notice.*