

GTC-265-FE / GTC-269-FE

5.0 / 9.0 Megapixel HD Network IP Fish Eye Camera

KEY FEATURES

- *1/2.9" / 1/1.7" Progressive CMOS
- *H.265 / H.264 / MJPEG video compression
- *Up to 5MP (2160*2160) / 9MP (3000*3000) resolution
- *Day / Night auto switch
- *IR range up to 5M
- *IP64 rating



TECHNICAL SPECIFICATIONS



Model No.	GTC-265-FE	GTC-269-FE
Image Sensor	1/2.9" Progressive CMOS	1/1.7" Progressive CMOS
Min. Illumination	Color 0.01lux @ f1.2(AGG ON) B/W 0 lux @ IR ON	
Shutter time	1/5 s ~ 1/20,000 s	
Lens	1.1MM, Angle of view:360°	2.0MM, Angle of view:360°
F No.	F2.0±5%	F2.4±5%
Day& Night	IR cut filter with auto switch	
Wide Dynamic Range	Digital WDR	
Video Compression	H.265/H.264	
Video bit rate	8Kbps~8Mbps	8Kbps~16Mbps
Video bit rate	256K~8M	
Triple Stream	Yes	
Frame Rate	Mainstream 5MP(2160*2160), 1520*1520, 1080*1080, 720*720	Mainstream 9MP(3000*3000), 2560*2560, 2160*2160, 1520*1520, 1080*1080, 720*720
	Substream 720*720, 480*480, 240*240	Substream 2MP(1080*1080), 720*720, 480*480, 240*240
	Mobilestream 480*480, 240*240	Mobilestream 480*480, 240*240
Image Settings	Rotate Mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable	
BLC	Support	
ROI	Support	
Video Analytics	NA	
Protocols	TCP / IP, HTTP, DHCP, DNS, DDNS, RTP / RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP	
Security	Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, IP address filtering	
System Compatibility	ONVIF(Ver 2.6)	

Communication Interface	1 RJ45 10M / 100M Ethernet interface	
LED	3pcs(SMD)	
IR Range	Up to 5M	
SD Storage	Yes	
Alarm Trigger	Yes	
Audio	Yes	
Video Output	Yes	
Reset Button	Yes	
POE	Yes	
Weatherproof	IP64	
Power Supply	DC 12V / POE	
Power Consumption	≤ 5W	≤ 7W
Dimensions	ø120*55MM	
Weight	Approx. 400g	
Storage Temperature	-30 °C ~ +60 °C	
Operating Temperature	-30 °C ~ +55 °C	

**Design and specifications are subject to change without prior notice.*